



Model : ZN8-DANTVF59L

Specification

Model	ZN8-DANTVF59L
Image sensor	1/3" Progressive Scan CMOS
Max. Resolution	2688x1520 / 2560x1440 @15fps 2304x1296 @20fps 1920x1080 @30fps
White Balance	Auto
Shutter Speed	1/5 – 1/20000
Day/Night	TRUE Day/Night
IR LED	12 pcs / 15-20 m. (Smart IR)
Min. Illumination	Color 0.05Lux (AGC ON); B/W 0Lux
WDR	Digital WDR
Defog	Yes
Lens	3.0 – 12.0mm (Auto Iris)
Max. Aperture	F1.4
F.O.V	87° ~ 35°
Audio In/Out	No
Network	1 Ethernet (10/100 Base-T) RJ-45 Connector
Image Compression	H.264 High/Main/Baseline Profile, MJPEG

Protocol	IPv4, IPv6, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, PPoE, Unicast and Multicast supported.
Resolution	Stream 1 : 2688x1520 : 2560x1440 : 2304x1296 : 1920x1080 Stream 2 : 720P to VGA
Web Browser	Yes
Security	User security authentication, Reset, Hardware WatchDog
SDK	Yes
VMD	Yes
Alarm Trigger	Motion Detection, Line Crossing, Tamper, Area Intrusion, Network disconnect, Disk alarm
Alarm Event	Message display, I/O output, Email snapshot
Power Consumption	PoE 12VDC, 24VAC
microSD Card	Max 64GB
Operating Temperature	-20°C ~ +60°C / 0% - 90% RH
ONVIF	Profile S
Weight	900g
Dimensions	φ 130 × 112mm
IP Class	IP66
Certifications	FCC / CE

