

Camera Mini Dome IP resolution 4 Megapixel built-in IR LED



Model: ZN8-MANTFN4L

Specification

Model:	ZN8-MANTFN4L
Image Sensor	1/3" Progressive Scan CMOS
Max. Resolution	2688*1520/2560*1440/15fps, 2304*1296/20fps, 1920x1080/30fps
White Balance	Auto
Shutter Speed	1/5-1/20000
Day & Night	TRUE Day/Night
IR LED	1 pcs/6-7 m. (Smart IR)
Min. illumination	Color 0.2Lux ; B/W 0Lux IR on
WDR	Digital WDR
Defog	Yes
Lens	3.6mm
Max. Aperture	F2.0
F.O.V	75°
Audio I/O	G711 ALAW / ULAW / RAW PCM
Network	1 Ethernet (10/100 Base-T) RJ-45 Connector
Image Compression	H.264 High/Main/Baseline Profile, MJPEG
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness

Protocols:	IPv4, IPv6, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, PPoE, Unicast and Multicast supported.
Resolution	Stream 1: 1920 x 1080 Stream 2: D1 to VGA
Web Browser	Yes
Security	User security authentication, Reset, Hardware WatchDog
SDK	Yes
VMD	Yes
Alarm Trigger	Motion Detection, Line Crossing, Tamper, Area Intrusion, Network disconnect, Disk alarm
Alarm Event	Message display, I/O output, Email snapshot
Power Consumption	PoE (IEEE802.3af) 12VDC
microSD Card	Max 32GB
Operating Temperature	-20°C~+55°C/0%-90% RH
ONVIF	Profile S
Weight	650g
Dimensions	φ100X53mm
IP Class	IP65
Certifications	FCC/CE

