

Camera 3 Megapixel Outdoor IR Dome



Model: ZN-D5DTMP58LHE

Specification

Model:	ZN-D5DTMP58LHE
Image Sensor	1/2.8" Sony ExmorR CMOS
Max. Resolution	2048 x 1536 30fps, 1920 x 1080 60fps
Shutter Speed	Manual 1/4~1/2000 Auto 1/25(30)~1/5000
Day & Night	Removable IR Cut Filter
IR LED	18 pcs.
Min. illumination	0 lx with IR LED ON
WDR	True-WDR
Lens	Motorized lens 3~10.5 mm
Network	10BASE-T, 100BASE-TX, RJ45
Video Compression	H.264, MJPEG : Image quality: 100 Steps(Q value)
Protocols:	IPv4, HTTP, SMTP, UPnP, DNS, RTSP, DDNS, RTP, TCP, UDP, RTCP, DHCP, ARP, FTP, IGMP, ICMP, NTP
Analog Video Out, (Installation Only)	CVBS Output, Stereo Jack
Web Browser	Internet Explorer 9.0 or above, Firefox, Chrome. Smart Phone (iOS, Android)
3D DNR	Yes (Depends on Codec Configuration)
Optical Zoom	3.5x
Digital Zoom	2 ~ 10x(Client Software)

Network Resolution	2048 x 1536, 1920 x 1080(Full HD), 1280 x 1024(SXGA), 1024x768(XGA), 1280 x 720(720p), 640 x 480(VGA), 640x360(HVGAW), 704x480/576(4CIF), 352x240/288(CIF)
Security	Password Protection
ROI	TBD
SDK(API)	HTTP based API, ONVIF Profile S
VMD, (Video Motion Detection)	User set 4 ROI(Region Of Interest), 30 Step Sensitivity
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player.
Alarm Trigger	VMD, External Alarm input
Alarm Event	E-mail notification(Snapshot), FTP transfer(Snapshot), External Alarm Out
Power Supply	DC12V/PoE(IEEE802.3af)
Edge Storage	SD / SDHC, up to 32GB
Weight	1.21kg
Dimensions	Ø 135 X 145(H), Ø 90(Dome) mm Ø 5.3 X 5.7(H), Ø 3.5(Dome) inch
IP Class	IP66

